

SHORT-INFO

# V 24 mobile

**The digital TIG inverter welding system for applications on the go.**

- TipTronic
- Superior mobility
- pulse and fast pulse up to 2 kHz
- LorchNet connection
- Low energy consumption



## At a glance

### **Outstanding TIG welding characteristics thanks to inverter technology**

Distinguished by their high efficiency and superb welding characteristics, inverters utilise digital software control technology that has a significant influence on the outcome of the welding process.

### **remote control**

Welders often experience that the conditions on site do not allow them to place their welding machine right beside them. When faced with this type of situation, they find the use of a remote control helpful as it allows them to intervene and adjust the welding current if necessary. This is why Lorch has included a large variety of different hand and foot remote controls in their V series, which are ready for use right away thanks to their plug&play support.

### **LorchNET connection**

All machines of Lorch's V series come with a LorchNet connection. This digital data interface provides standardised communication and ensures that all components located in a Lorch automation system understand each other perfectly thanks to Plug&Weld technology.

### **Aluminium welding (AC/DC variant)**

Positive polarity ignition and automatic cap shape produce a perfectly shaped arc during aluminium welding. The special amplitude of the alternating current combined with an optimised current balance yields an excellent cleaning effect and a manageable weld pool.

### **Powerful**

Working in the background, cutting-edge processor technology ensures that the gas pre-flow, the shaping of the arc and the control of the welding current work together seamlessly during welding. The result of this smooth interaction are superior duty cycle levels and increased productivity.

## Benefits

### **The SmartBase expert database provides for optimum arc conditions**

SmartBase is the name of the expert database devised by Lorch to control the arc. This database lets you adjust the parameter settings yourself, giving you the freedom you need to tweak and correct even the finest details of the process you are applying.

### **Low energy consumption**

The included on-demand function automatically turns the components of your Lorch V 24 mobile on and off as needed. Thermal control sensors monitor the temperature of the components and regulate the speed of the fan accordingly. This smart technology reduces fan noise and dust levels in the machine compartment and helps conserve energy.

### **Pulse and fast pulse up to 2 kHz**

The standard pulse function with up to 2 kHz that is built into every machine offers you additional benefits when welding thin plates.

### **Plain text display with language selection and TipTronic**

Thanks to the clearly structured user interface and the slanted operating panel, the device control remains well visible throughout operation and affords the user an ergonomic operating position. You select the AC or DC function, the electrode diameter and the welding current based on the machine you are using. When working in TipTronic mode, you can then save your ideal setting for each weld.

### **Automatic final current reduction**

Lorch's automatic final current reduction produces perfectly clean weld ends by filling the end crater.

### **Mobility**

Our Lorch V 24 mobile with trolley wheelset will meet all your mobility needs as it allows you to both carry the unit and move it on its wheels.

## Controlconcept

### **Standard**

- "3 steps to weld" operating concept
- Infinitely variable current setting
- Can be operated by remote control
- TipTronic



**Technical Data: V-Serie**

	<b>V 24</b>	<b>V 24 mobil</b>	<b>V 27</b>	<b>V 30</b>	<b>V 30 mobil</b>	<b>V 40</b>	<b>V 50</b>
<b>TIG</b>							
welding range (in Amps)	3-240	3-240	3-270	3-300	3-300	3-400	3-500
current setting	infinitely variable	infinitely variable	infinitely variable	infinitely variable	infinitely variable	infinitely variable	infinitely variable
<b>Electrode</b>							
weldable electrodes (mm)	1,5-4,0	1,5-4,0	1,5-4,0	1,5-6,0	1,5-6,0	1,5-6,0	1,5-6,0
<b>Duty cycle TIG DC</b>							
duty cycle 100% (in Amps) - DC	220	220	250	250	270	360	380
duty cycle 60% (in Amps) - DC	240	240	270	300	300	400	500
duty cycle at max. current (in %) - DC	60%	60%	60%	60%	60%	60%	60%
<b>Duty cycle TIG AC (only AC systems)</b>							
duty cycle 100% (in Amps) - AC	210	190	250	250	240	360	380
duty cycle 60% (in Amps) - AC	230	220	270	300	280	400	500
duty cycle at max. current (in %) - AC	50%	50%	60%	60%	50%	60%	60%
<b>Mains</b>							
mains voltage (in V)	400	400	400	400	400	400	400
phases (50/60 Hz)	3~	3~	3~	3~	3~	3~	3~
positive mains tolerance (in %)	15%	15%	15%	15%	15%	15%	15%
negative mains tolerance (in %)	15%	15%	15%	15%	15%	15%	15%

mains fuse (in Amps)	16	16	16	32	16	32	32
mains plug	CEE 16	CEE 16	CEE 16	CEE 32	CEE 16	CEE 32	CEE 32

Dimensions and weights

dimensions (LxWxH) (in mm)	1130x450x815	812x283x518	1130x450x815	1130x450x815	812x283x518	1130x450x860	1130x450x860
weight (in kg)	84,6/90,5	29,4/35,1	85,0/92,0	86,4/93,6	31,0/37,0	107,6/121,5	108,7/123,2
weight, water cooling (filled) (in kg)	14,7	---	14,7	14,7	---	14,7	14,7

Standards and approvals

standard	EN 60974-01	EN 60974-01	EN 60974-01	EN 60974-01	EN 60974-01	EN 60974-01	EN 60974-01
protection class (EN 60529)	IP23	IP23	IP23	IP23	IP23	IP23	IP23
insulation class	F	F	F	F	F	F	F
designation	CE, S	CE, S	CE, S	CE, S	CE, S	CE, S	CE, S